

[Back to main](#)

[Back to Yaesu](#)

[Next HF and more](#)

(C) 2000-2018
by SMOOFV

Last modified 2017-09-29



SPECIFICATIONS

GENERAL

Type:	Amateur HF transceiver
Frequency range:	TX: 10-160 m RX: 10-160 m and 10-10.5 / 26.9-27.5 MHz
Tuning steps:	Continuous
Mode:	AM/SSB/CW
Channels/memory management:	
Repeater shift/offset:	No
Power supply:	Mains 12 VDC
Current drain/power consumption:	RX: 600 mA @ 12 VDC

TX: Max 21 A @ 12 VDC

Antenna impedance/connector:	50-75 ohms / SO-239
Dimensions (W*H*D):	334*148*284 mm (13.15*5.83*11.18")
Weight:	13.6 Kg (29.98 lbs)

Other features:

RECEIVER SECTION

Receiver system:	? conversion superheterodyne 1st IF: ? MHz 2nd IF: ? KHz
Sensitivity:	0.3 uV (10 dB S/N)
Selectivity:	AM/SSB/CW: 2.4 KHz (-6 dB), 4 KHz (-60 dB) CW with optional filter: 600 Hz (-6 dB), 1.2 KHz (-60 dB)
Image rejection:	
AF output power/speaker:	? W at ?% distortion / ? ohms
External speaker connector:	

TRANSMITTER SECTION

RF output power:	AM: 80 W (input) SSB: 260 W(PEP input) CW: 180 W (input)
Modulation system:	
FM deviation:	No FM
Spurious emissions:	Less than -? dB
Microphone impedance/connector:	? ohms / ?-pin

MISCELLANEOUS

Manufactured:	Japan, 197x-197x (Discontinued)
Additional info:	
Related documents:	
Modifications:	
Options/Accessories:	- -